

MIAMI NEW S1PL FO SR ESD

KU085NR

CE EN ISO 20345:2022 S1PL FO SR ESD

LOW SAFETY SHOE

35-47

KUBE Supergrip

Safety sandal, in Nubuck IDROTECH® WRU flower leather 1.8-2.0 mm thick. Highly breathable and abrasion resistant fabric lining. Closure with a velcro strap.

FOOTWEAR ENTIRELY WITHOUT METAL PARTS

PUNTALE 200J Thermic **polymer-based** composite according to EN 22568

LAMINATE PL flexible anti-perforation composite fabric according to EN 22568

KUBE polyurethane sole bidensity antistatic, hydrolysis resistant ISO 5423:92, to hydrocarbons and abrasion, shock-resistant and slip-resistant

SOLE 5000 trimaterial extracomfort, breathable, removable, anatomical, absorbent, ESD and antibacterial

Footwear meets the requirement in accordance with IEC 61340-4-3:2017 (IEC 61340-5-1:2016) for electrical resistance ESD

FO resistance of the sole to hydrocarbons

SR Resistance to slippage

Size 35-47 **Shoe weight** Tg 42 **gr. 495**

* The calculated weight excludes laces and insoles.



AREAS OF APPLICATION

- Logistics and Light Industry
- Automotive Components
- Metal and Wood Carpentry
- ESD Area

CERTIFICATIONS APPLIED

- PL** Puncture Resistance with Non-Metallic Insert (nail Ø 4.5mm)
- E** Heel Energy Absorption
- FO** Hydrocarbon Resistance
- WRU** Water-Repellent Upper
- DGUV 112-191** DGUV 112-191

TECHNOLOGIES AND MATERIALS

- NO METAL** No metal
- ESD** ESD - Electrostatic Discharge
- NO METAL** Metal-Free
- HIGH VISIBILITY** High Visibility
- AIR** High Breathability
- MONDO POINT 11** Mondo Point 11
- EXTRA LIGHT** Extreme Lightness
- SR** Slip Resistance (optional glycerin test)

ANTI-SLIP RESULTS

*after simulation of walking by slight abrasion

| | | | | | |
|-------------------------------------|---|---|-----------------------------------|---|---|
| Ceramic tile floor with NaLS | Forward heel (heel slip 7°) ≥ 0.31 0.55 | Backward heel (heel slip 7°) ≥ 0.36 0.45 | Ceramic tile floor with glycerin | Forward heel (heel slip 7°) ≥ 0.19 0.31 | Backward heel (heel slip 7°) ≥ 0.22 0.34 |
| SRA on ceramic tile floor with NaLS | forward flat slip ≥ 0.32 0.39 | Forward Heel forward flat slip (7°) ≥ 0.28 0.37 | SRB on steel floor with glycerine | forward flat slip ≥ 0.18 0.30 | Forward Heel forward flat slip (7°) ≥ 0.13 0.20 |

↳ SOLE

KUBE Supergrip

Kube is a safety shoe with a young and sporty style, featuring a special highly slip resistant compound and specific inverted-profile cube-shaped lugs on the tread. Combined, these elements provide exceptional resistance on the slipperiest surfaces. This work shoe is therefore ideal for indoor environments. The sole is designed with reduced volume and height, ensuring both a lightweight feel and a look suitable for everyday wear. Thanks to its outstanding slip resistance, Kube has earned numerous field awards and passed rigorous tests—including the one for roof work (formerly UNI 11583:2015), one of the most challenging slip tests.

