

END SERIES

DANCE S1P

KU055HF

CE UNI EN ISO 20345:2012 S1P SRC ESD

LOW SAFETY SHOE

35-42

KUBE Supergrip

Low safety shoe, suede back leather thickness 1,8 - 2,0 mm
External 3D fabric, perspiring and abrasion resistant.
Soft, lined and padded tongue.

COMPLETELY METAL FREE SHOE

TOECAP 200J polymeric **composite non-thermic** according to EN 12568

MIDSOLE flexible antiperforation composite fabric according to EN 12568

SOLE KUBE bidensity polyurethane antistatic, resistant to hydrolysis ISO

5423:92, to hydrocarbons and to abrasion, anti-shock and anti-slipping **SRC**

INSOLE 5000, three-materials extracomfort: perspiring, removable, anatomic, absorbing, ESD and anti-bacterial

The shoe satisfies the requirement according to the norm IEC 61340-4-3:2017 (IEC 61340-5-1:2016) for the electrical resistance **ESD**

Size 35-42 Shoe weight Sz 42 gr. 485

** The calculated weight excludes laces and insoles.*



→ **AREAS OF APPLICATION**

- Logistics and Light Industry
- Automotive Components
- Metal and Wood Carpentry
- ESD Area

→ **CERTIFICATIONS APPLIED**

- Slip Resistant Sole
- Heel Energy Absorption
- Hydrocarbon Resistance

→ **TECHNOLOGIES AND MATERIALS**

- No metal
- ESD - Electrostatic Discharge
- Metal-Free
- High Breathability
- Mondo Point 11
- Extreme Lightness

→ **ANTI-SLIP RESULTS**

**after simulation of walking by slight abrasion*

Ceramic tile floor with NaLS	Forward heel (heel slip 7°) <div style="border: 1px solid black; padding: 2px; display: flex; justify-content: space-between;"> ≥ 0.31 0.55 </div>	Backward heel (heel slip 7°) <div style="border: 1px solid black; padding: 2px; display: flex; justify-content: space-between;"> ≥ 0.36 0.45 </div>	Ceramic tile floor with glycerin	Forward heel (heel slip 7°) <div style="border: 1px solid black; padding: 2px; display: flex; justify-content: space-between;"> ≥ 0.19 0.31 </div>	Backward heel (heel slip 7°) <div style="border: 1px solid black; padding: 2px; display: flex; justify-content: space-between;"> ≥ 0.22 0.34 </div>
SRA on ceramic tile floor with NaLS	forward flat slip <div style="border: 1px solid black; padding: 2px; display: flex; justify-content: space-between;"> ≥ 0.32 0.39 </div>	Forward Heel forward flat slip (7°) <div style="border: 1px solid black; padding: 2px; display: flex; justify-content: space-between;"> ≥ 0.28 0.37 </div>	SRB on steel floor with glycerine	forward flat slip <div style="border: 1px solid black; padding: 2px; display: flex; justify-content: space-between;"> ≥ 0.18 0.30 </div>	Forward Heel forward flat slip (7°) <div style="border: 1px solid black; padding: 2px; display: flex; justify-content: space-between;"> ≥ 0.13 0.20 </div>

↳ SOLE

KUBE Supergrip

Kube is a safety shoe with a young and sporty style, featuring a special highly slip resistant compound and specific inverted-profile cube-shaped lugs on the tread. Combined, these elements provide exceptional resistance on the slipperiest surfaces. This work shoe is therefore ideal for indoor environments. The sole is designed with reduced volume and height, ensuring both a lightweight feel and a look suitable for everyday wear. Thanks to its outstanding slip resistance, Kube has earned numerous field awards and passed rigorous tests—including the one for roof work (formerly UNI 11583:2015), one of the most challenging slip tests.

