

# YORK S3

KU061D

CE UNI EN ISO 20345:2012 S3 SRC

**LOW SAFETY SHOE**

**35-49**

**KUBE** Supergrip

Low safety shoe, back WRU leather thickness 1,8-2,0 mm.  
 Perspiring and abrasion resistant fabric lining.  
 Shoe with refracting fabric insert.  
 Soft, lined and padded tongue.

**TOECAP 200J** polymeric **composite non-thermic** according to EN 12568

**MIDSOLE flexible antiperforation composite fabric** according to EN 12568

**SOLE KUBE** bidensity polyurethane antistatic, resistant to hydrolysis ISO 5423:92,

to hydrocarbons and to abrasion, anti-shock and anti-slipping **SRC**

**INSOLE 4001**, Comfort insole, perspiring, removable, anatomic, absorbing, antistatic ed antibacterial. Electrical resistance: *the values found prove that this insole is ESD*

**Size 35-49 Shoe weight Sz 42 gr. 500**

*\* The calculated weight excludes laces and insoles.*



## AREAS OF APPLICATION



Logistics and Light Industry

Automotive Components

Metal and Wood Carpentry

## CERTIFICATIONS APPLIED



Slip Resistant Sole



Heel Energy Absorption



Hydrocarbon Resistance



Water-Repellent Upper

## TECHNOLOGIES AND MATERIALS



No metal



High Visibility



Mondo Point 11



Extreme Lightness

## ANTI-SLIP RESULTS

*\*after simulation of walking by slight abrasion*

Ceramic tile floor with NaLS	<b>Forward heel</b> (heel slip 7°) ≥ 0.31 <b>0.55</b>	<b>Backward heel</b> (heel slip 7°) ≥ 0.36 <b>0.45</b>	Ceramic tile floor with glycerin	<b>Forward heel</b> (heel slip 7°) ≥ 0.19 <b>0.31</b>	<b>Backward heel</b> (heel slip 7°) ≥ 0.22 <b>0.34</b>
SRA on ceramic tile floor with NaLS	<b>forward flat slip</b> ≥ 0.32 <b>0.39</b>	<b>Forward Heel</b> forward flat slip (7°) ≥ 0.28 <b>0.37</b>	SRB on steel floor with glycerine	<b>forward flat slip</b> ≥ 0.18 <b>0.30</b>	<b>Forward Heel</b> forward flat slip (7°) ≥ 0.13 <b>0.20</b>

↳ SOLE

## KUBE Supergrip

Kube is a safety shoe with a young and sporty style, featuring a special highly slip resistant compound and specific inverted-profile cube-shaped lugs on the tread. Combined, these elements provide exceptional resistance on the slipperiest surfaces. This work shoe is therefore ideal for indoor environments. The sole is designed with reduced volume and height, ensuring both a lightweight feel and a look suitable for everyday wear. Thanks to its outstanding slip resistance, Kube has earned numerous field awards and passed rigorous tests—including the one for roof work (formerly UNI 11583:2015), one of the most challenging slip tests.

