

OXFORD S3

KU068D

CE UNI EN ISO 20345:2012 S3 SRC

ANKLE SAFETY SHOE

35-49

KUBE Supergrip

High safety shoe, back WRU leather thickness 1,8-2,0 mm.

Perspiring and abrasion resistant fabric lining.

Shoes with refracting fabric insert.

Soft, lined and padded tongue.

The shoe satisfies the requirements of slipping resistance on inclined roofs according to **UNI 11583:2015**

TOECAP 200J polymeric **composite non-thermic** according to EN 12568

MIDSOLE flexible antiperforation composite fabric according to EN 12568

SOLE KUBE bidensity polyurethane antistatic, resistant to hydrolysis ISO 5423:92,

to hydrocarbons and to abrasion, anti-shock and anti-slipping **SRC**

INSOLE 4001, Comfort insole, perspiring, removable, anatomic, absorbing, antistatic ed antibacterial. Electrical resistance: *the values found prove that this insole is ESD*

THIS PRODUCT COMPLIES WITH THE REQUIREMENTS OF THE STANDARD ASTM F2413-24:

Impact resistant footwear (I)

Compression resistant footwear (C)

Puncture Resistant Footwear (PR)

Slip Resistance (SRO)

Size 35-49 Shoe weight Sz 42 gr. 540

** The calculated weight excludes laces and insoles.*

↳ **AREAS OF APPLICATION**



Sloped Roofs



Logistics and Light Industry



Automotive Components



Metal and Wood Carpentry

↳ **CERTIFICATIONS APPLIED**



ASTM F2413-24



Slip Resistant Sole



Heel Energy Absorption



Hydrocarbon Resistance



Water-Repellent Upper

↳ **TECHNOLOGIES AND MATERIALS**



No metal



High Visibility



Mondo Point 11



Extreme Lightness



Slip Resistance on Inclined Roofs

↳ **ANTI-SLIP RESULTS**

**after simulation of walking by slight abrasion*

Ceramic tile floor with NaLS	Forward heel (heel slip 7°)	≥ 0.31 0.55	Backward heel (heel slip 7°)	≥ 0.36 0.45	Ceramic tile floor with glycerin	Forward heel (heel slip 7°)	≥ 0.19 0.31	Backward heel (heel slip 7°)	≥ 0.22 0.34
	forward flat slip	≥ 0.32 0.39	Forward Heel forward flat slip (7°)	≥ 0.28 0.37		forward flat slip	≥ 0.18 0.30	Forward Heel forward flat slip (7°)	≥ 0.13 0.20
SRA on ceramic tile floor with NaLS					SRB on steel floor with glycerine				

↳ SOLE

KUBE Supergrip

Kube is a safety shoe with a young and sporty style, featuring a special highly slip resistant compound and specific inverted-profile cube-shaped lugs on the tread. Combined, these elements provide exceptional resistance on the slipperiest surfaces. This work shoe is therefore ideal for indoor environments. The sole is designed with reduced volume and height, ensuring both a lightweight feel and a look suitable for everyday wear. Thanks to its outstanding slip resistance, Kube has earned numerous field awards and passed rigorous tests—including the one for roof work (formerly UNI 11583:2015), one of the most challenging slip tests.

