

QUEBEC S3 CI HI WR HRO

HR178E

CE UNI EN ISO 20345:2012 S3 CI HI WR HRO SRC

SAFETY BOOT

39-47

HARD ROCK ANTISTATIC Durability

Calf safety boot, WRU anti-scratch leather thickness 1,8-2,0 mm. Soft Windtex® water resistant membrane lining, with very good perspiration and abrasion resistance.

Boot with refracting fabric insert.

Soft, lined and padded tongue.

TOECAP 200J polymeric **composite non-thermic** according to EN 12568

MIDSOLE flexible antiperforation composite fabric according to EN 12568

SOLE HARD ROCK ANTISTATIC bidensity polyurethane and antistatic **RUBBER**.

Sole resistant to hydrocarbons and to abrasion, anti-shock and anti-slipping **SRC**

INSOLE 5000, three-materials extracomfort: perspiring, removable, anatomic, absorbing, ESD and anti-bacterial

CI cold insulation of sole complex -17°C

HI heat insulation of sole complex

WR water resistant shoe

HRO resistance to hot contact of the outsole

Boot height sole included 23 cm

Size 39-47 Boot weight Sz 42 gr. 750

** The calculated weight excludes laces and insoles.*



AREAS OF APPLICATION

- Farming and Agriculture
- Cold Environments
- Construction and Building Sites
- Hydrocarbons and Chemicals
- Metal and Wood Carpentry

CERTIFICATIONS APPLIED

- HRO Sole Resistance +300**
- Slip Resistant Sole
- Heel Energy Absorption
- Hydrocarbon Resistance
- Water-Repellent Upper
- Water-Repellent Footwear
- Heat Insulating Outsole

TECHNOLOGIES AND MATERIALS

- No metal
- WindTex® Membrane
- High Visibility
- Mondo Point 11
- Cold Insulating Outsole
- Scratch-Resistant Leather

ANTI-SLIP RESULTS

**after simulation of walking by slight abrasion*

Ceramic tile floor with NaLS	Forward heel (heel slip 7°)	Backward heel (heel slip 7°)	Ceramic tile floor with glycerin	Forward heel (heel slip 7°)	Backward heel (heel slip 7°)
	≥ 0.31 0.46	≥ 0.36 0.53		≥ 0.19 0.20	≥ 0.22 0.20
SRA on ceramic tile floor with NaLS	forward flat slip	Forward Heel forward flat slip (7°)	SRB on steel floor with glycerine	forward flat slip	Forward Heel forward flat slip (7°)
	≥ 0.32 0.40	≥ 0.28 0.40		≥ 0.18 0.22	≥ 0.13 0.17

↳ PLUS



WindTex® Membrane

The Windtex® membrane is a technology designed to block water and wind. Lightweight and elastic, it provides comfort and protection throughout the workday while maintaining a stable microclimate between the skin and fabric. Thanks to its high breathability, it is ideal for breathable safety shoes that need to prevent overheating and excessive sweating even in winter or during long shifts.



Scratch-Resistant Leather

Zero Abrasion technology uses leather finished with multiple layers of polyurethane to protect the upper from scratches, cuts, and wear. This solution ensures that the footwear maintains flawless performance and appearance even after months of intense use, providing advanced resistance against abrasive surfaces and mechanical environments—all while preserving foot comfort and breathability.

↳ SOLE

HARD ROCK ANTISTATIC Durability

The Hard Rock Antistatic PU line is designed to protect safety footwear in industrial environments where extreme temperatures and hazardous materials can pose serious risks to workers. The combination of an antistatic nitrile rubber sole and certified technical materials ensures reliable protection in high-risk settings. This line also features soft lines and lightweight volumes, offering a minimal design that prioritizes comfort and practicality without compromising safety.

