

3PU PATENTED

END SERIES

GHIBLI S1PL FO SR

3R182T

CE EN ISO 20345:2022 S1PL FO SR

LOW SAFETY SHOE

36-47

3RUN Agility

Holed low safety shoe, back suede leather thickness 1,8-2,0 mm.
Highly perspiring and abrasion resistant fabric lining.
Shoe with refracting fabric insert.
Soft and lined tongue.

COMPLETELY METAL FREE SHOE






TOECAP 200J polymeric composite **non-thermic** according to EN 22568
PL MIDSOLE flexible antiperforation composite fabric according to EN 22568
SOLE 3RUN three-densities polyurethane antistatic, resistant to hydrolysis ISO 5423:92, to hydrocarbons and to abrasion, anti-shock and anti-slipping SRC
ANTITORSION insert in the sole to assure stability on uneven ground
INSOLE MEMORY, extra comfort trimaterial insole with soft PU Memory foam cushion that relieves fatigue in the heel and resists body pressure. Breathable, removable, anatomical, absorbent, antibacterial, and ESD.
FO sole resistance to hydrocarbons
SR sole resistance against slipping





Size 36-47 Shoe weight Sz 42 gr. 510

** The calculated weight excludes laces and insoles.*


↪ **AREAS OF APPLICATION**

-  **Logistics and Light Industry**
-  **Automotive Components**
-  **Metal and Wood Carpentry**

↪ **CERTIFICATIONS APPLIED**

-  **PL Puncture Resistance with Non-Metallic Insert (nail Ø 4.5mm)**
-  **Heel Energy Absorption**
-  **Hydrocarbon Resistance**
-  **DGUV 112-191**

↪ **TECHNOLOGIES AND MATERIALS**

-  **No metal**
-  **Metal-Free**
-  **High Visibility**
-  **High Breathability**
-  **Mondo Point 11**
-  **Extreme Lightness**
-  **Slip Resistance (optional glycerin test)**
-  **Leather**
-  **Three to be™ - Triple Density Injection**
-  **Anti-Torsion Sole**

↪ **ANTI-SLIP RESULTS**

**after simulation of walking by slight abrasion*

| | | | | | |
|------------------------------|---------------------------------------|--|----------------------------------|---------------------------------------|--|
| Ceramic tile floor with NaLS | Forward Heel (heel slip 7°) | Backward heel (heel slip 7°) | Ceramic tile floor with glycerin | Forward Heel (heel slip 7°) | Backward heel (heel slip 7°) |
| | ≥ 0.31 0.44 | ≥ 0.36 0.44 | | ≥ 0.19 0.24 | ≥ 0.22 0.24 |

↳ PLUS



Three to be™ - Triple Density Injection

Three to Be® - Tripla Densità Iniettata technology represents one of the most advanced results of our R&D efforts. Patented by Giasco, it integrates three entirely polyurethane-injected sole layers to optimize safety shoe performance in terms of comfort, stability, and slip resistance.



Anti-Torsion Sole

The Anti Torsion system uses a thermoplastic shank designed to increase stability on irregular and wet surfaces. Unlike standard shanks, it flexes with the foot's natural motion, reducing the risk of twists and falls. Ideal for outdoor work, especially in construction, where surface control is critical.

↳ SOLE

BRUN Agility

3Run is a sporty and youthful line developed for those who work both indoors and outdoors on regular surfaces. Specifically, the design of this safety shoe is inspired by running shoes, combining soft volumes with sharp lines. The tread, on the other hand, is designed for indoor use. This is made possible by a dense pattern of lugs that together provide excellent slip resistance for this safety shoe.

