

# KENT S3

AC061D

CE UNI EN ISO 20345:2012 S3 SRC

**LOW SAFETY SHOE**

**36-51**

**ACTION Essential**

Low safety shoe, WRU back leather thickness 1,8-2,0 mm.  
 Perspiring and abrasion resistant fabric lining.  
 Shoe with refracting fabric insert.  
 Soft, lined and padded tongue.

**TOECAP 200J** polymeric **composite non-thermic** according to EN 12568

**MIDSOLE flexible antiperforation composite fabric** according to EN 12568

**SOLE ACTION** bidensity polyurethane antistatic, resistant to hydrolysis ISO 5423:92, to hydrocarbons and to abrasion, anti-shock and anti-slipping **SRC**

**INSOLE EASY 4001**, Comfort insole, perspiring, removable, anatomic, absorbing, antistatic ed antibacterial. Electrical resistance: *the values found prove that this insole is ESD*

**Size 36-51 Shoe weight Tg 42 gr. 595**

*\* The calculated weight excludes laces and insoles.*



→ **AREAS OF APPLICATION**

- Farming and Agriculture
- Construction and Building Sites
- Logistics and Light Industry
- Automotive Components
- Metal and Wood Carpentry

→ **CERTIFICATIONS APPLIED**

- Slip Resistant Sole
- Heel Energy Absorption
- Hydrocarbon Resistance
- Water-Repellent Upper

→ **TECHNOLOGIES AND MATERIALS**

- No metal
- High Visibility
- Mondo Point 11
- Extreme Lightness

→ **ANTI-SLIP RESULTS**

*\*after simulation of walking by slight abrasion*

Ceramic tile floor with NaLS	<b>Forward heel</b> (heel slip 7°) <div style="border: 1px solid black; padding: 2px; display: flex; justify-content: space-between;"> <span>≥ 0.31</span> <span style="background-color: black; color: yellow; padding: 2px;">0.48</span> </div>	<b>Backward heel</b> (heel slip 7°) <div style="border: 1px solid black; padding: 2px; display: flex; justify-content: space-between;"> <span>≥ 0.36</span> <span style="background-color: black; color: yellow; padding: 2px;">0.44</span> </div>	Ceramic tile floor with glycerin	<b>Forward heel</b> (heel slip 7°) <div style="border: 1px solid black; padding: 2px; display: flex; justify-content: space-between;"> <span>≥ 0.19</span> <span style="background-color: black; color: yellow; padding: 2px;">0.32</span> </div>	<b>Backward heel</b> (heel slip 7°) <div style="border: 1px solid black; padding: 2px; display: flex; justify-content: space-between;"> <span>≥ 0.22</span> <span style="background-color: black; color: yellow; padding: 2px;">0.22</span> </div>
SRA on ceramic tile floor with NaLS	<b>forward flat slip</b> <div style="border: 1px solid black; padding: 2px; display: flex; justify-content: space-between;"> <span>≥ 0.32</span> <span style="background-color: black; color: yellow; padding: 2px;">0.37</span> </div>	<b>Forward heel</b> (heel slip 7°) <div style="border: 1px solid black; padding: 2px; display: flex; justify-content: space-between;"> <span>≥ 0.28</span> <span style="background-color: black; color: yellow; padding: 2px;">0.33</span> </div>	SRB on steel floor with glycerine	<b>forward flat slip</b> <div style="border: 1px solid black; padding: 2px; display: flex; justify-content: space-between;"> <span>≥ 0.18</span> <span style="background-color: black; color: yellow; padding: 2px;">0.22</span> </div>	<b>Forward heel</b> (heel slip 7°) <div style="border: 1px solid black; padding: 2px; display: flex; justify-content: space-between;"> <span>≥ 0.13</span> <span style="background-color: black; color: yellow; padding: 2px;">0.24</span> </div>

↳ SOLE

## **ACTION** Essential

The Action line is designed for those who work outdoors every day and need a shoe that is simple yet effective. With soft lines and a lightweight structure, it offers a minimal design that prioritizes comfort and practicality without compromising on safety. Perfect for daily tasks and light maintenance, these shoes support every step without weighing you down.

