

# VERDI R S3

AC880BRP

CE UNI EN ISO 20345:2012 S3 SRC

ANKLE SAFETY SHOE

39-47

**ACTION** Essential

High safety shoe, water-resistant WRU leather thickness 1,8-2,0 mm. Perspiring and abrasion resistant fabric lining. Shoe with refracting fabric insert. Lined and padded tongue. Shoe with fast device.

**TOECAP 200J** polymeric **composite non-thermic** according to EN 12568

**MIDSOLE antiperforation steel** according to EN 12568

**SOLE ACTION** bidensity polyurethane antistatic, resistant to hydrolysis ISO 5423:92, to hydrocarbons and to abrasion, anti-shock and anti-slipping **SRC**  
**INSOLE EASY 4001**, Comfort insole, perspiring, removable, anatomic, absorbing, antistatic ed antibacterial. Electrical resistance: *the values found prove that this insole is ESD*

**Size 39-47 Shoe weight Sz 42 gr. 560**

*\* The calculated weight excludes laces and insoles.*



## AREAS OF APPLICATION

- Farming and Agriculture
- Construction and Building Sites
- Logistics and Light Industry
- Automotive Components
- Metal and Wood Carpentry



## CERTIFICATIONS APPLIED

- Slip Resistant Sole
- Heel Energy Absorption
- Hydrocarbon Resistance
- Water-Repellent Upper

## TECHNOLOGIES AND MATERIALS

- High Visibility
- Mondo Point 11
- Extreme Lightness
- Quick Release
- Steel Plate

## ANTI-SLIP RESULTS

*\*after simulation of walking by slight abrasion*

Ceramic tile floor with NaLS	<b>Forward heel</b> (heel slip 7°) <div style="border: 1px solid black; padding: 2px; display: inline-block;"> <span style="margin-right: 10px;">≥ 0.31</span> <span style="background-color: black; color: yellow; padding: 2px 5px;">0.48</span> </div>	<b>Backward heel</b> (heel slip 7°) <div style="border: 1px solid black; padding: 2px; display: inline-block;"> <span style="margin-right: 10px;">≥ 0.36</span> <span style="background-color: black; color: yellow; padding: 2px 5px;">0.44</span> </div>	Ceramic tile floor with glycerin	<b>Forward heel</b> (heel slip 7°) <div style="border: 1px solid black; padding: 2px; display: inline-block;"> <span style="margin-right: 10px;">≥ 0.19</span> <span style="background-color: black; color: yellow; padding: 2px 5px;">0.32</span> </div>	<b>Backward heel</b> (heel slip 7°) <div style="border: 1px solid black; padding: 2px; display: inline-block;"> <span style="margin-right: 10px;">≥ 0.22</span> <span style="background-color: black; color: yellow; padding: 2px 5px;">0.22</span> </div>
SRA on ceramic tile floor with NaLS	<b>forward flat slip</b> <div style="border: 1px solid black; padding: 2px; display: inline-block;"> <span style="margin-right: 10px;">≥ 0.32</span> <span style="background-color: black; color: yellow; padding: 2px 5px;">0.37</span> </div>	<b>Forward heel</b> (heel slip 7°) <div style="border: 1px solid black; padding: 2px; display: inline-block;"> <span style="margin-right: 10px;">≥ 0.28</span> <span style="background-color: black; color: yellow; padding: 2px 5px;">0.33</span> </div>	SRB on steel floor with glycerine	<b>forward flat slip</b> <div style="border: 1px solid black; padding: 2px; display: inline-block;"> <span style="margin-right: 10px;">≥ 0.18</span> <span style="background-color: black; color: yellow; padding: 2px 5px;">0.22</span> </div>	<b>Forward heel</b> (heel slip 7°) <div style="border: 1px solid black; padding: 2px; display: inline-block;"> <span style="margin-right: 10px;">≥ 0.13</span> <span style="background-color: black; color: yellow; padding: 2px 5px;">0.24</span> </div>

↳ SOLE

## **ACTION** Essential

The Action line is designed for those who work outdoors every day and need a shoe that is simple yet effective. With soft lines and a lightweight structure, it offers a minimal design that prioritizes comfort and practicality without compromising on safety. Perfect for daily tasks and light maintenance, these shoes support every step without weighing you down.

