

3PU PATENTED

NEW

GHIBLI NEW S1PL FO SR

3R174V

CE EN ISO 20345:2022+A1:2024 S1PL FO SR ESD

LOW SAFETY SHOE

36-47

3RUN Agility

Low safety shoe made of suede split leather, thickness 1.8-2.0 mm. Lining in highly breathable and abrasion-resistant fabric. Footwear with reflective insert. Padded lined tongue.

SHOE ENTIRELY METAL FREE

TOE CAP 200J composite polymer-based, **non-thermal**, according to EN 22568.

MIDSOLE PL flexible anti-perforation composite fabric, according to EN 22568.

SOLE 3RUN triple-density polyurethane, antistatic, resistant to hydrolysis ISO 5423:92, hydrocarbons, and abrasion; anti-shock and slip resistant.

ANTI-TORSION Insert in the sole to ensure stability on uneven surfaces.

INSOLE MEMORY tri-material extra comfort insole with soft PU memory foam cushion in the heel, fatigue-reducing and resistant to body pressure.

Breathable, removable, anatomical, absorbent, antibacterial, and **ESD**.

The footwear meets the requirements according to IEC 61340-4-3:2017 (IEC 61340-5-1:2016) for **ESD** electrical resistance.

FO Sole resistant to hydrocarbons.

SR Slip resistance.

Size: 36-47 **Weight** (size 42): **525g**

** The calculated weight excludes laces and insoles.*



→ **AREAS OF APPLICATION**

- Logistics and Light Industry
- Automotive Components
- Metal and Wood Carpentry
- ESD Area

→ **CERTIFICATIONS APPLIED**

- PL** Puncture Resistance with Non-Metallic Insert (nail Ø 4.5mm)
- E** Heel Energy Absorption
- FO** Hydrocarbon Resistance
- DGUV 112-191**

→ **TECHNOLOGIES AND MATERIALS**

- No metal**
- ESD** - Electrostatic Discharge
- SR** Slip Resistance (optional glycerin test)
- Leather**
- Three to be™** - Triple Density Injection

→ **ANTI-SLIP RESULTS**

**after simulation of walking by slight abrasion*

Ceramic tile floor with NaLS	Forward Heel (heel slip 7°)	Backward heel (heel slip 7°)	Ceramic tile floor with glycerin	Forward Heel (heel slip 7°)	Backward heel (heel slip 7°)
	≥ 0.31 0.44	≥ 0.36 0.44		≥ 0.19 0.24	≥ 0.22 0.24

↳ PLUS



3PU PATENT

Three to be™ - Triple Density Injection

Three to Be® - Tripla Densità Iniettata technology represents one of the most advanced results of our R&D efforts. Patented by Giasco, it integrates three entirely polyurethane-injected sole layers to optimize safety shoe performance in terms of comfort, stability, and slip resistance.

↳ SOLE

3RUN Agility

3Run is a sporty and youthful line developed for those who work both indoors and outdoors on regular surfaces. Specifically, the design of this safety shoe is inspired by running shoes, combining soft volumes with sharp lines. The tread, on the other hand, is designed for indoor use. This is made possible by a dense pattern of lugs that together provide excellent slip resistance for this safety shoe.

